



Lonking 龙工

CDM6210W WHEEL EXCAVATOR

Efficiency Rules the Future



TECHNICAL PARAMETERS

	Name	Data
Basic	Operating weight	20850 kg
	Boom length	5600 mm
	Arm length	3000 mm
	Standard bucket	1.17 m ³
	Max.Travel speed	32 km/h
	Max.Swing speed	13.5 rpm
	Grade ability	31°(60%)
	Tire type	10.0-20-14PR
	Max.Traction force	96.6 kN
Engine	Engine model	6BTAA5.9-C150-II
	Rated power	112 kW/1950 rpm
	Displacement	5.9 L
	Fuel tank	350 L
	Max.Torque	614/1500 N.m/rpm
Hydraulic	Max.Flow(total)	280×2 L/min
	Max.Working pressure	35 MPa
	Max.Digging force	149 kN
	Hrdraulic oil tank	250 L
Working Range	A1 Max.Digging reach	9970 mm
	B1 Max.Ground digging reach	9750 mm
	C1 Max.Digging height	9850 mm
	D1 Max.Dumping height	6930 mm
	E1 Max.Digging depth	6420 mm
	F1 Max.Vertical digging depth	4370 mm
	G1 Min. Working radius	3645 mm
Overall Dimension	Transport demission (A×B×C)	9430×2530×3290 mm
	D Counterweight ground clearance	1300 mm
	E Min. Ground clearance	350 mm
	F Tail swing radius	2785 mm
	G Axle base	2850 mm
	H Wheel base	1944 mm

PRODUCT FEATURES

Cummins turbocharged direct injection engine with strong power and fuel-efficient.
 Charge air cooling system with parallel radiator.
 Fully hydrostatic driven, 2 speed power shift transmission
 Piston travel motor with variable displacement and high torque provide smooth travel.
 Hub reduction type front steering axle and rear rigid axle.
 Advanced hydraulic system with function of interflow & re-activation, swing priority.
 Comfortable ROPS cabin with 2.7m³ operating space.
 Equipped with large LCD display, air conditioner, bluetooth radio, suspension seat. More comfortable driving operation.
 Heavy-duty undercarriage frame, Dozer and outrigger can be installed interchangeably.

OPTIONAL

Custom buckets
Hydraulic hammer
Quick coupler
Work warning light
Protecting net
Front protecting net

For more information on Lonking products, Please contact our local agent:

The following blank can be used for notes or comments.

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not be used without written permission. 2024/03

Specifications and design are subject to change without prior notice. Machines shown may not include optional accessories.

Lonking (FU JIAN) INTERNATIONAL TRADE CO., LTD.
Lonking Holdings Limited
 Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai
 Tel: +86-21-3760 2242 E-mail:export@lonking.cn
<http://www.lonkinggroup.com>

- OPERATING WEIGHT: 20850 kg
- ENGINE POWER: 112 kW
- BUCKET CAPACITY: 1.17 m³
- TRAVEL SPEED: 32 km/h